

2022/01

High Cost Effective Genset

Powered by Baudouin / Voltage 380-415V / 50Hz / 3P

Product Model	Prime Power		Standby Power		Engine Model	Fuel Cons. @75% load	Noise Level dB(A) @7m	Product Appearance
	kVA	kW	kVA	kW				
B18SE3	18	14	20	16	4M08G2D3/5	3.7	66.8	
B20SE3	20	16	23	18	4M08G4D3/5	5.2	67.0	
B30SE3	30	24	38	30	4M08G8D3/5	6.8	67.4	
B38SE3	38	30	42	33	4M08G10D3/5	7.6	67.5	
B60SE3	63	52	69	55	4M06G2D3/5	12.6	68.1	
B80SE3	80	64	88	70	4M10G2D3/5	13.5	68.6	
B100SE3	100	80	113	90	4M10G4D3/5	16.0	70.1	
B125SE3	125	100	150	120	4M12G2D3/5	21.8	72.4	
B150SE3	150	120	165	132	4M12G4D3/5	23.3	73.0	
B200SE3	200	160	225	180	6M12G4D3/5	30.8	74.2	
B250SE3	250	200	275	220	6M12G8D3/5	40.1	74.2	
B310SE3	313	250	350	280	6M16G8D3/5	47.7	75.7	
B375SE3	375	300	400	320	6M21G2D3/5	59.6	76.8	
B500SE3	500	400	550	440	6M21G8D3/5	80.5	77.5	
B650SE3	650	520	725	580	6M33G6D3/5	110.4	77.8	
B750SE3	750	600	713	650	6M33G8D3/5	122.0	78.2	
B1250E3C	1250	1000	1375	1100	12M33G8D3/5	209.2	79.6	
B1500E3C	1500	1200	1650	1320	12M33G12D3/5	247.8	81.5	
B1875E3C	1875	1500	2063	1650	16M33G6D3/5	307.2	83.2	
B2000E3C	2000	1600	2250	1800	16M33G8D3/5	335.1	84.6	
B2250E3C	2250	1800	2500	2000	20M33G4D3/5	384.7	86.1	
B2500E3C	2500	2000	2750	2200	12M55G4D3/5	427.7	87.4	
B2750E3C	2750	2200	3000	2400	12M55G6D3/5	469.1	88.3	
B3000E3C	3000	2400	3313	2650	16M55G2D3/5	510.1	89.2	

Note: About detailed technical information, please contact PowerLink to get technical data sheet and drawing.



www.powerlinkworld.com

E-mail: info@powerlinkworld.com

Note: For more information, please call us or contact your local agent.

Document NO. : 20220110

